

**Signature Series Premium Water Conditioner** utilizes two separate media chambers in one tank by using the patented Vortech™ Tank distributor technology. Using the Mid-Plate Vortech™ two chamber tank with Activated Carbon in the top chamber saves space, increases efficiency and extends the life of the ion-exchange resin. Two water treatment processes with only one tank and controller. Simply Smarter!

**Top Chamber----Coconut Shell-High Activated Carbon (CS-HAC)**


- Removes chlorine and other chemicals before they enter your home
- Neutralizes unpleasant odors and discoloration of water
- Reduces the drying effects of chlorine for healthier skin and hair
- Eliminates chlorine corrosion of fixtures and appliances
- Improves air quality by preventing the release of chemical vapors
- Keeps clothes softer, brighter and more colorful
- Carbon can be replaced without replacing softener resin

**Bottom Chamber---- High Efficiency Ion-Exchange Resin (HCR) Provides all of the soft water advantages of a conventional water softener by eliminating hard water effects**

**Standard Features:**

- Regenerates When Needed, Based On Water Usage
- 1" High Flow Design with 1" Vortech™ Distributor
- Double "Polished" Backwashing
- Corrosion Resistant Components
- No Fasteners, Screws Or Bolts
- Single Motor Driven Piston Operation
- Circuit Board Is Enclosed And Separated From Salt Tank
- Premium Grade Ion Exchange Resin
- Lifetime Seamless Fiberglass Wrapped Resin Tank
- Thermal Tank Shroud – Black With Black Trim\*
- Soft Water Brine Tank Refill
- 15" x 17" Brine Tank-Dry Salt-Grid System-Safety Shut-Off

\*No jacket available for 13 x 54 media tank



**Brine System Tank Options**

| Type        | Shape     | Dimensions | Amt. Salt | Models  |
|-------------|-----------|------------|-----------|---------|
| Compact     | Square    | 11" x 36"  | 150 lbs.  | 100     |
| Space Saver | Rectangle | 15" x 17"  | 240 lbs.  | 100-150 |
| Round       | Round     | 18" x 40"  | 320 lbs.  | 100-150 |

## PRODUCT SPECIFICATIONS

| Model No. | Media Carbon | Cu. Ft. Resin | Grains of Capacity |          | Grains/ lb. Salt | Cont FR 15 psi drop | Media Tank Dia X Ht. | Iron Reduction* | Pipe Con. Size | Max Drain Flow gpm | Drain Size | Distributor Type | Brine Line Size |
|-----------|--------------|---------------|--------------------|----------|------------------|---------------------|----------------------|-----------------|----------------|--------------------|------------|------------------|-----------------|
|           |              |               | Salt Setting       | Capacity |                  |                     |                      |                 |                |                    |            |                  |                 |
| 2PMP100C  | 1.0          | 1.0           | 8 lb.              | 24,000   | 3,000            | 12 gpm              | 9 x 48               | 3 ppm           | 1" or 3/4"     | 2.7                | 5/8"       | Vortech™         | 3/8"            |
| 2PMP150C  | 1.5          | 1.5           | 12 lb.             | 36,000   | 3,000            | 16 gpm              | 13 x 54              | 3 ppm           | 1" or 3/4"     | 4.2                | 5/8"       | Vortech™         | 3/8"            |

## ADDITIONAL OPERATING INFORMATION

Not intended to be used to treat water that is Microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Installation must comply with all state and local codes.

|                                     |                          |                |
|-------------------------------------|--------------------------|----------------|
| Operating Water Temperature Range   | Max 100°                 | Minimum 40°    |
| Operating Ambient Temperature Range | Max 120°                 | Minimum 40°    |
| Operating Pressure Range            | Max 125 psi              | Minimum 20 psi |
| Electrical components               | 110v - 60 hz 0.5 Amperes |                |

# Simply Soft Water Treatment System Limited Warranty

## Warranty Policy

Lee Supply Corp. warrants this water treatment system as stated herein:

From the date of shipment, when we receive any part (or parts) described below, during the specified period below, which we find defective because of faulty materials or workmanship or corrosion, we will repair or replace the part (or parts) and return it to the customer. The customer pays only freight to and from our repair facility and local labor and / or service charges.

- 
- **Five Years On All Parts**
  - **Ten Years On Control Valve**
  - **Ten Years on Mineral Tank**
  - **Lifetime on Brine Tank**
- 

## General Conditions

Damage to any part of this water treatment system because of misuse, misapplication, neglect, alteration, accident, shipment or operation contrary to our printed instructions, or damage caused by accident, freezing, flood, fire or Acts of God, is not covered by this warranty. In all such cases, regular parts and service charges apply.

We assume no warranty liability in connection with this water treatment system other than specified herein. This warranty is in lieu of all other warranties, expressed or implied, including warranties of fitness for a particular purpose. We do not authorize any person or representative to assume for us any other obligations on the sale of this water treatment system.

This warranty becomes effective on the shipment date of the covered system. Should a malfunction occur, contact Lee Supply Corp. or an authorized dealer.

This warranty applies to the original owner at the original location. This warranty is transferable to subsequent owners or locations only with prior written consent by Lee Supply Corp. Prior to written consent on transferring this warranty the system may require inspection by a service technician from Lee Supply Corp. or one authorized by Lee Supply Corp.

Owners Name \_\_\_\_\_

Installer \_\_\_\_\_

Installation Address \_\_\_\_\_ City \_\_\_\_\_ St. \_\_\_\_\_ Zip \_\_\_\_\_

Model No. \_\_\_\_\_

Serial No. \_\_\_\_\_

Date Of Installation \_\_\_\_\_ Dealer Name \_\_\_\_\_

Marketed Exclusively By:

Lee Supply Corp.  
6610 Guion Road  
Indianapolis, IN 46268  
800.873.1103

**SIMPLY SOFT**<sup>®</sup>  
Professional Water Treatment Products