

Signature Series Premium Models

Standard Features:

- Regenerates When Needed, Based On Water Usage
- 1" High Flow Design
- 1" Vortech™ Distributor
- Double "Polished" Backwashing
- Corrosion Resistant Components
- No Fasteners, Screws Or Bolts
- Single Motor Driven Piston Operated
- Circuit Board Is Enclosed And Separated From Salt Tank
- Premium Grade Ion Exchange Resin
- Lifetime Seamless Fiberglass Wrapped Resin Tank
- Thermal Tank Shroud – Black With Black Trim
- Soft Water Brine Tank Refill
- 15" x 17" Brine Tank
- Safety Shut-Off
- Dry Salt-Grid System

Options:

- Choice of pipe connections (in 3/4" or 1")
- Rain cover for outdoor installations



| Type | Shape | Dimensions | Amt. Salt | Models |
|-------------|-----------|------------|-----------|---------|
| Compact | Square | 11" x 36" | 150 lbs. | 100-150 |
| Space Saver | Rectangle | 15" x 17" | 240 lbs. | 100-200 |
| Round | Round | 18" x 40" | 320 lbs. | 100-200 |

PRODUCT SPECIFICATIONS

| Model No. | Media Cu. Ft. | Grains of Capacity | | Grains/ lb. Salt | Cont FR 15 psi drop | Peak FR 25 psi drop | Media Tank Dia X Ht. | Iron Reduction* | Pipe Con. Size | Max Drain Flow gpm | Drain Size | Distributor Type | Brine Line Size |
|-----------|---------------|--------------------|----------|------------------|---------------------|---------------------|----------------------|-----------------|----------------|--------------------|------------|------------------|-----------------|
| | | Salt Setting | Capacity | | | | | | | | | | |
| 2P-SS 100 | 1.0 | 8 lb. | 24,000 | 3,000 | 12 gpm | 18 gpm | 9 x 48 | 3 ppm | 1" or 3/4" | 1.7 | 5/8" | Vortech™ | 3/8" |
| 2P-SS 150 | 1.5 | 12 lb. | 36,000 | 3,000 | 14 gpm | 20 gpm | 10 x 54 | 3 ppm | 1" or 3/4" | 2.2 | 5/8" | Vortech™ | 3/8" |
| 2P-SS 200 | 2.0 | 16 lb. | 48,000 | 3,000 | 18 gpm | 25 gpm | 12 x 52 | 3 ppm | 1" or 3/4" | 3.2 | 5/8" | Vortech™ | 3/8" |
| 2P-SS 250 | 2.5 | 20 lb. | 60,000 | 3,000 | 19 gpm | 26 gpm | 13 x 54 | 3 ppm | 1" or 3/4" | 4.2 | 5/8" | Vortech™ | 3/8" |

ADDITIONAL OPERATING INFORMATION

Not intended to be used to treat water that is Microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Installation must comply with all state and local codes.

See manufacturer's warranty sheet for details on warranty

Operating Water Temperature Range
 Operating Ambient Temperature Range
 Operating Pressure Range
 Electrical components
 Parts or Service

Max 100°
 Max 120°
 Max 125 psi
 110v - 60 hz 0.5 Amperes
 Contact Dealer or Lee Supply for location and phone of Authorized Dealer

Simply Soft Water Treatment System Limited Warranty

Warranty Policy

Lee Supply Corp. warrants this water treatment system as stated herein:

From the date of shipment, when we receive any part (or parts) described below, during the specified period below, which we find defective because of faulty materials or workmanship or corrosion, we will repair or replace the part (or parts) and return it to the customer. The customer pays only freight to and from our repair facility and local labor and / or service charges.

-
- **Five Years On All Parts**
 - **Ten Year On Control Valve**
 - **Lifetime on Mineral Tank**
 - **Lifetime on Brine Tank**
-

General Conditions

Damage to any part of this water treatment system because of misuse, misapplication, neglect, alteration, accident, shipment or operation contrary to our printed instructions, or damage caused by accident, freezing, flood, fire or Acts of God, is not covered by this warranty. In all such cases, regular parts and service charges apply.

We assume no warranty liability in connection with this water treatment system other than specified herein. This warranty is in lieu of all other warranties, expressed or implied, including warranties of fitness for a particular purpose. We do not authorize any person or representative to assume for us any other obligations on the sale of this water treatment system.

This warranty becomes effective on the shipment date of the covered system. Should a malfunction occur, contact Lee Supply Corp. or an authorized dealer.

This warranty applies to the original owner at the original location. This warranty is transferable to subsequent owners or locations only with prior written consent by Lee Supply Corp. Prior to written consent on transferring this warranty the system may require inspection by a service technician from Lee Supply Corp. or one authorized by Lee Supply Corp.

Owners Name _____

Installer _____

Installation Address _____ City _____ St. _____ Zip _____

Model No. _____

Serial No. _____

Date Of Installation _____ Dealer Name _____

Marketed Exclusively By:

Lee Supply Corp.
6610 Guion Road
Indianapolis, IN 46268
800.873.1103

SIMPLY SOFT[®]
Professional Water Treatment Products